

Hilumz® Utility Lighting Solutions

SELECTION GUIDE: *Fixture-Specific LED Conversion Kits*

HOLOPHANE®



GranVille® Classic

Housing: Concave tapered w/leaf pattern
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
Button photocell
Wireless controls
DALI-enabled driver w/antenna

GranVille® Premiere

Housing: Flared fluted base w/swing-open door
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell receptacle
Wireless controls
DALI-enabled driver w/antenna

Arlington®

Housing: Flared fluted base w/octagon top cage
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell receptacle
Wireless controls
DALI-enabled driver w/antenna

HOLOPHANE[®] continued**Jefferson[®]**

Housing: Flared fluted base w/octagon top cage w/spurs
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell receptacle
Wireless controls
DALI-enabled driver w/antenna

**Washington-Acrylic**

Housing: Fluted base w/swing-open door
Replaces: 70W up to 400W lamp
LED Watts: 50W up to 200W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Washington-Glass**

Housing: "Enhanced" convex rounded floral
Replaces: 70W up to 400W lamp
LED Watts: 50W up to 200W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

HOLOPHANE® continued**Taft**

Housing: Fluted base w/round top cage w/4 arms
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell receptacle
Wireless controls
DALI-enabled driver w/antenna

**Esplanade®**

Housing: Round w/4 ribs and ribbed top capital
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Memphis®**

Housing: Round w/4 ribs and smooth round top
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

HOLOPHANE[®] continued**Hallbrook[®] Pendant**

Housing: Straight slanted w/Hinge Top
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Bern Pendant**

Housing: Convex pendant w/Hinge Top
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Prague Pendant**

Housing: Concave pendant w/Hinge Top
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

COOPER® Lighting**Generation® Architectural Base (GAT or ARC)**

Housing: Smooth convex base, 2 arm cage w/top hat
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Generation® Classical Base (GLC or CLB)**

Housing: Grooved concave base, mult. cage top options
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Generation® Acorn Base (GAR or ACN)**

Housing: Grooved flared base w/grooved neck, mult. cages
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

COOPER® Lighting continued**ANE Acorn (a.k.a. Westminster)**

Housing: Narrow convex base with leaf pattern
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**MNC Manchester**

Housing: Grooved flared base w/grooved neck, mult. cages
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**Cascade**

Housing: Grooved convex base, hexagon top with six arms
Center vertical reflector (reflector stays w/retrofit)
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

COOPER® Lighting continued**Traditionaire®**

Housing: Square lantern style w/4 arms
 Replaces: 50W up to 250W lamp
 LED Watts: 30W up to 120W
 CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
 Input Volts: 120/277VAC or 480VAC
 Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
 Install: Matching plugs & bolt patterns
 Optional: 10 kV surge protection
 7-pin photocell
 Wireless controls
 DALI-enabled driver w/antenna

**Epic Classical**

Housing: Straight slanted w/Hinge Top
 Replaces: 70W up to 400W lamp
 LED Watts: 30W up to 200W
 CCT's: 50K, 40K, 30K, Amber
 Input Volts: 120/277VAC or 480VAC
 Optical Pattern: Type 5, Type 4, Type 3
 Install: Matching bolt patterns
 Optional: 10 kV surge protection
 7-pin photocell
 Wireless controls
 DALI-enabled driver w/antenna

GE® Lighting**Torch**

Housing: Grooved flared base w/smooth neck
 Replaces: 50W up to 250W lamp
 LED Watts: 30W up to 120W
 CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
 Input Volts: 120/277VAC or 480VAC
 Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
 Install: Matching plugs & bolt patterns
 Optional: 10 kV surge protection
 7-pin photocell
 Wireless controls
 DALI-enabled driver w/antenna

King Luminaire®**K118 Washington**

Housing: Grooved flared base w/smooth neck
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

**K56 Cleveland**

Housing: Octagon lantern w/8 arms
Bottom pole mount or top pendant mount options
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell receptacle
Wireless controls
DALI-enabled driver w/antenna

**K56 Tudor**

Housing: Octagon lantern w/8 arms with top & bottom spurs
Bottom pole mount or top pendant mount options
Replaces: 50W up to 250W lamp
LED Watts: 30W up to 120W
CCT's: 50K, 40K, 35K, 30K, 27K, 22K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5 (360°) or Type 3 (Street-side only)
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell receptacle
Wireless controls
DALI-enabled driver w/antenna

LUMEC®



Renaissance Teardrop

Housing: Round w/4 ribs and smooth round top cylinder
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna

Sternberg®



Omega

Housing: Convex pendant with cylinder top fitter
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna



1950 Mission Trails

Housing: Convex pendant with grooved tapered top fitter
Replaces: 70W up to 400W lamp
LED Watts: 30W up to 200W
CCT's: 50K, 40K, 30K, Amber
Input Volts: 120/277VAC or 480VAC
Optical Pattern: Type 5, Type 4, Type 3
Install: Matching plugs & bolt patterns
Optional: 10 kV surge protection
7-pin photocell
Wireless controls
DALI-enabled driver w/antenna